




Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AMA3-IE3 132S2**

Rated power **6.6 kW S1 Duty**

Speed **3504 rpm**

Voltage **480 / 820V**

Frequency **60 Hz**

Connection **Delta / Star**

Full load current **10.1 A / 5.86 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M25 x 1.5**

Construction **Aluminium**

Weight **49.5 Kg**

Type number

Warranty

Efficiency class **IE3**

Load data **100%**

Efficiency **89.2 %**

Power factor **0.88**

Sound pressure level (1m) **75 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **18 Nm**

Starting / Full load torque **2.5**

Pull up / Full load torque

Pull out / Full load torque **2.7**

Starting / Full load current (DOL) **9.1**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **6308**

Bearing NDE **6308**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk