




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAS-SR-IE2 90 S2
Rated power	1.5 kW S1 Duty
Speed	2880 rpm
Voltage	220V
Frequency	50 Hz
Connection	Single Phase
Full load current	8.2 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Aluminium
Weight	15.5 Kg
Type number	
Warranty	
Run Capacitor	40uf/450V
Start Capacitor	200uf/250V

Efficiency class	IE2
Load data	100%
Efficiency	81.3 %
Power factor	0.98
Sound pressure level (1m)	78 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	4.97	Nm
Starting / Full load torque	2.3	
Pull up / Full load torque		
Pull out / Full load torque	2.1	

Starting / Full load current (DOL)	
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6205
Bearing NDE	6203

Protection Device **Thermal Reset Switch**

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk