




Specification
Manufacturer AmTecs
Motor type AM1-IE2 180M4
Rated power 22.2 kW S1 Duty
Speed 1758 rpm
Voltage 480 / 820V
Frequency 60 Hz
Connection Delta / Star
Full load current 34 A / 19.7 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M32 x 1.5
Construction Cast Iron
Weight 172 Kg
Type number
Warranty

Efficiency class IE2
Load data 100%
Efficiency 91.2 %
Power factor 0.86
Sound pressure level (1m) 81 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 121 Nm
Starting / Full load torque 2.5
Pull up / Full load torque
Pull out / Full load torque 3.0

Starting / Full load current (DOL) 8.3
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6311
Bearing NDE 6211

AmTecs Ltd

Charnham Park, Hungerford
Berkshire, RG17 0YT

Tel: +44 (0) 1488 686970

Fax: +44 (0) 1488 686968

sales@amtecs.co.uk

www.amtecs.co.uk