




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AM1-IE2 160L2**
 Rated power **18.5 kW S1 Duty**
 Speed **2937 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **33 A / 19.1 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M32 x 1.5**
 Construction **Cast Iron**
 Weight **135 Kg**
 Type number
 Warranty

Efficiency class **IE2**
 Load data **100%**
 Efficiency **90.9 %**
 Power factor **0.89**
 Sound pressure level (1m) **81 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **60 Nm**
 Starting / Full load torque **2.3**
 Pull up / Full load torque
 Pull out / Full load torque **3**

Starting / Full load current (DOL) **7.6**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6209**
 Bearing NDE **6209**

AmTecs Ltd

Charnham Park, Hungerford
Berkshire, RG17 0YT

Tel: +44 (0) 1488 686970

Fax: +44 (0) 1488 686968

sales@amtecs.co.uk

www.amtecs.co.uk