




Specification
Manufacturer AmTecs
Motor type AMA-IE2 100L4
Rated power 2.64 kW S1 Duty
Speed 1728 rpm
Voltage 277 / 480V
Frequency 60 Hz
Connection Delta / Star
Full load current 8.09 A / 4.65 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 31 Kg
Type number
Warranty

Efficiency class IE2
Load data 100%
Efficiency 84.3 %
Power factor 0.81
Sound pressure level (1m) 61 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 14.6 Nm
Starting / Full load torque 2.2
Pull up / Full load torque
Pull out / Full load torque 2.3

Starting / Full load current (DOL) 7.4
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6206
Bearing NDE 6206

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
sales@amtecs.co.uk www.amtecs.co.uk	